

	A	B	C	D
1	Description	Imperial (US)	Metric	Note
2	Manufacturer	Kymco		Taiwan (<i>actually manufactured in China</i>)
3	Model Name	Like 150i with ABS		
4	Model Code	TE30AN		The only place this shows up is on the VIN sticker on the right side of the scooter
5	Model Year	2021		Release in Spring of 2021
6	MSRP	\$3,099		Plus Dealer Prep, Destination Charge, Sales Tax, Title, Registration, Tag
7	VIN Number			Located on tag under frame between rear shocks, 17 characters
8	Month and Year Manufactured			Located on tag under frame between rear shocks
9	Engine Number			Located on Left side of crank case casting, 4 plus 7 characters
10	Overall Length	75.394	1915	Inches / Millimeters
11	Overall Width	26.772	680	Inches / Millimeters
12	Overall Height	44.488	1130	Inches / Millimeters
13	Ground Clearance	4.724	120	Inches / Millimeters
14	Wheel Base	51.772	1315	Inches / Millimeters
15	Minimum turning radius	47.638	1210	Inches / Millimeters
16	Seat Height	31.102	790	Inches / Millimeters
17	Curb Weight (dry)	264	120	Pounds / Kilograms
18	Weight (wet)	284	128	Pounds / Kilograms
19	Maximum weight capacity	633.6	288	Pounds / Kilograms
20	Engine Oil (exchange)	0.211	0.8	Gallons / Liters
21	Transmission (exchange)	0.032	0.12	Gallons / Liters
22	Fuel Tank	1.796	6.8	Gallons / Liters
23	Miles Per Unit	85	36.14	Miles per Gallon / Kilometers per Liter
24	Fuel Range (<i>estimated</i>)	153	244.8	Miles / Kilometers
25	Fuel Weight	11.23	5.10	pounds/kilograms 1 gallon of gasoline weighs 6.073 to 6.417 pounds.
26	Maximum Speed (<i>approximate</i>)	60 to 65	96 to 104	Miles per Hour / Kilometers per Hour
27				
28	Engine Type			Four Stroke, Air cooled, Single Cylinder, Overhead Cam, Four Valves
29	Displacement	9.14	149.8	Cubic Inches / Cubic Centimeters
30	Cylinder bore	2.32	59	Inches / Millimeters
31	Piston Stroke	2.16	54.8	Inches / Millimeters
32	Compression Ratio	10.9 to 1		
33	Ignition Type	ECU		Electronic Control Unit
34	Fuel	Gasoline	Petrol	92 octane unleaded gasoline
35	Fuel System	Port EFI		Valve Body Electronic Fuel Injection, ECU (Electronic Control Unit)
36	Standard Spark Plug	CR8E		
37	Idle Speed	1,700		RPM (Revolution per Minute) Plus or Minus 100
38	Cooling System	Forced Air		
39	Maximum Power	13.87	10.2	Horsepower / Kilowatts (at 8,000 RPM)
40	Maximum Torque	110.62	150	Foot-Pounds / Newton-Meters (at 7,000 RPM)
41	Starting System	Electric		
42				
43	Electrical System	12		Volt
44	Note: <i>Specifications are cut short at this point because the KYMCO wiring diagram has so many errors.</i>			
45				